

**TECHNICAL DATA****PRODUCT****ACRYLIC METALLIC**
Exterior Interior**DESCRIPTION**

Metallic paints with very good brushing qualities and spread properties. The unusual mica pigment dries to a metallic sheen, which can be polished to a high shine. Pale Gold, Bright Gold, Antique Gold, Copper, Pewter, Silver, Pearlescent

APPLICATION

Ensure all surfaces are sound, clean, dry and free from rust and contamination.

Porous surfaces: Prime and seal first with a suitable primer.

Previously painted: lightly abrade before application to provide a key.

Non-porous surfaces: prime first with a suitable primer.

Ferrous metal: prime first with a suitable anti-corrosive primer.

Use a similar base coat colour to greatly increase the covering power.

Ensure the product is well mixed.

Apply 2-3 coats as required with a good quality brush.

Light reflection will accentuate brush marks and imperfections in the background.

The covering ability of this paint will vary with the colour. It is essential to do a test area before application.

Applying in high temperatures or direct sunlight will affect drying time. Do not apply when rain is imminent.

Protect from extremes of temperature

On bare wood lightly sand the first coat to remove grain raising.

Take care to eliminate brush/roller marks by over brushing. Brush marks will be highlighted by the metallic sheen.

Stippling the wet surface with a stippling brush will produce a hammered finish.

Spay application will ensure a smooth metallic surface.

USES

Interior walls and plaster work, picture frames and mirror surrounds, interior - furniture and pottery,

Exterior metalwork - gates, railings and door furniture.

COVERAGE

Approx. 8 sq. m per litre 85 sq. ft per US qt

SHEEN LEVEL

Semi gloss

CONTAINERS

500ml, 1L, 4L. US Quart, US Gal.

No OF COATS

2/ 3 coats

DRYING TIME

15mins-1 hr, depending on temperature

RECOAT TIME

2hrs – 4hrs

CURING

5-7 days. Before placing heavy objects on surface.

CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, and allow to dry naturally.

FLAMMABILITY

No fire hazard before or during use, or in the cured state.

STORAGE

Protect from extremes of temperature during storage and application.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Further information may be obtained from:

POLYVINE LIMITED
Severn Distribution Park
Sharpness, Berkeley,
Gloucestershire.
GL13 9UQ
United Kingdom

Telephone No. 0845 017 1671
International +44 845 017 1671
Fax: 0845 017 1672
Email info@polyvine.co.uk

January 2010