



BONA TRAFFIC

Product Description

Features

Traffic is a two-component waterborne 100% polyurethane finish for the surface treatment of wooden floors in commercial premises where a very high resistance to wear is required. It is also suitable for overcoating factory pre-finished cork floors. Traffic Matt provides a clear natural appearance giving "invisible protection" and the look of an oiled floor but, unlike oil, offers years of virtually maintenance-free protection. Traffic Silk Matt has a higher sheen level but all the other qualities of the matt version.

- Contains less than 10% solvents
- Superb scratch and chemical resistance
- High scuff resistance
- Non-yellowing surface
- Meets DIN norm 18 032 and BS 7044:1990 for slip resistance
- Meets ÖNORM C 2354 Category C (very heavy wear)

Technical Data

Type of finish:	2-comp. waterborne 100% polyurethane finish
Solids content:	Approx. 33%
pH-value:	Approx. 8
Viscosity:	Approx. 24 sec. (25°C, FC4)
Resistance to wear:	Approx. 2.5 mg/100 revolutions (SIS 923509)
Sheen (at 60°):	Invisible Protection: approx. 15, Silk Matt: approx. 45
Mixing ratio:	1 part Traffic Hardener to 10 parts Traffic
Pot life:	5 hours at 20°C
Drying time:	3-4 hours at 20°C/60% R.H.
Application tools:	Roller or applicator
Application rate:	8-10 m ² /litre (120-100g/m ²) per coat
Safety	Finish: Unclassified Hardener: Classified (see the Safety Data Sheet)
Shelf life:	1 year, from date of production, in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size (incl. Hardener):	3 x 4.95 litres (36 boxes per pallet) 8 x 1.1 litre (54 boxes per pallet) - only "IP"