

M A T E R I A L   S A F E T Y   D A T A   S H E E T

PRODUCT NAME: BREAKTHROUGH SATIN WROUGHT IRON BLACK              HMIS    H F R P  
PRODUCT CODE: 50 90    CODES: 1\*1 0 G

=====  
SECTION I - MANUFACTURER IDENTIFICATION      =====

MANUFACTURER'S NAME: Vanex, Inc.                      NAME OF PREPARER : Tammy Maynor  
ADDRESS : P.O. Box 987  
    1700 South Shawnee Street  
    Mt. Vernon, IL 62864  
EMERGENCY PHONE : 618-244-1416                      DATE PRINTED : 08/22/01  
INFORMATION PHONE : 800-851-7390                      FORMULA REVISED : 06/21/01

=====  
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION      =====

REPORTABLE COMPONENTS CAS NUMBER	VAPOR PRESSURE mm Hg   @   Deg F	WEIGHT PERCENT
* BUTYL CELLOSOLVE 111-76-2 OSHA PEL: 50 PPM, OSHA TWA: 25 PPM, ACGIH TLV: 25 PPM	-subject to Sec. 313 .6            68	8
TALC (WITHOUT ASBESTOS) 14807-96-6 OSHA PEL: 20 MPPCF	0            68	<5%
# CARBON BLACK 1333-86-4 OSHA PEL: 3.5MG/M(3), OSHA TWA: 3.5MG/M(3), ACGIH TLV: 3.5MG/M(3)	-subject to Proposition 65 0            0	1.63
* ETHYLENE GLYCOL 107-21-1 OSHA TWA: 50 PPM, ACGIH TLV: 50 PPM	-subject to Sec. 313 .05          68	1
SILICA (QUARTZ) 14808-60-7 OSHA PEL: 10 MG/M(3), OSHA TWA: 0.1MG/M(3), ACGIH TLV: 0.1MG/M(3)	0            0	0.14

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

ADDITIONAL HAZARD WARNINGS:

# Detectable amounts of a chemical known to the State of California to cause cancer and/or birth defects or other reproductive harm may be present in this product. Refer to Section VI (HEALTH HAZARDS) for further information.

=====  
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS      =====

BOILING RANGE: 212 deg F - 340 deg F                      SPECIFIC GRAVITY (H2O=1): 1.10  
VAPOR DENSITY: HEAVIER THAN AIR                      WEIGHT PER GALLON: 9.20 lb/gl  
COATING V.O.C. (POUNDS): 2.00 lb/gl                      COATING V.O.C. (GRAMS): 240 g/l  
EVAPORATION RATE: Slower than ether.                      SOLUBILITY IN WATER: Miscible  
APPEARANCE AND ODOR: Waterborne liquid.

=====  
SECTION IV - FIRE AND EXPLOSION HAZARD DATA      =====

FLASH POINT: 210 deg F                                      METHOD USED: CLOSED CUP  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1                      UPPER: 10.6

EXTINGUISHING MEDIA: ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Wear positive-pressure, self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS

No unusual fire or explosion hazards are known for this product. As typical of closed containers containing liquid, they may explode when exposed to extreme heat.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE  
CONDITIONS TO AVOID  
Excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID)

Oxidizing material. Hydrofluoric acid is incompatible with the silica(s) in this product.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Combustion products: carbon dioxide, carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

50 90 PRODUCT NAME: BREAKTHROUGH SATIN WROUGHT IRON BLACK

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapors of this material may irritate nose, throat, and respiratory passages. Higher concentrations can induce headache, dizziness, nausea, drowsiness, and shortness of breath. Sneezing and dryness of mucous membranes.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN CONTACT: No irritation is likely to develop following short contact periods with human skin. Prolonged or repeated exposure can lead to redness, swelling and necrosis.

EYE CONTACT: This material can induce pain and moderate irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Adverse systemic effects can develop following repeated/prolonged contact with human skin.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Headache, nausea, drowsiness, fatigue. A single dose of this product is moderately toxic by ingestion.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Inhalation of high concentrations of vapor can induce anemia, liver and kidney injury and clouding of the cornea.

The silica(s) contained in this product can have the following effects:

ACUTE: Can cause upper respiratory irritation.

CHRONIC: Prolonged overexposure by inhalation may cause delayed lung injury/disease (silicosis). Take appropriate measures to avoid breathing dust.

CARCINOGENICITY INFORMATION, UNDER PROPOSITION 65 - STATE OF CALIFORNIA:

Carbon black is a chemical known to the state of California to cause

cancer.

CARCINOGENICITY:

NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED: No  
The International Agency for Research on Cancer (IARC) has concluded:  
Silica (quartz) can cause cancer based on animal data. (Risk from  
silica(s) depends on duration and level of exposure.) IARC has rated the  
silica(s) in this product Level 1. Carbon black is a possible human  
carcinogen rating it Level 2B.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Dermatitis. Pulmonary and/or pre-existing upper respiratory and lung  
diseases.

EMERGENCY AND FIRST AID PROCEDURES

SKIN: Remove contaminated clothing and footwear. Wash material off skin  
with soap and water. If redness, itching or a burning sensation  
develops, get medical attention. Wash contaminated clothing and  
decontaminate footwear before reuse.

EYES: Immediately flush with water for at least 15 minutes and have eyes  
examined and treated by medical personnel.

INGESTION: Give 1 or 2 glasses of water to drink. Induce vomiting.  
Refer victim to medical personnel.

INHALATION: Remove victim to fresh air. If cough or other respiratory  
symptoms develop, consult medical personnel.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====  
50 90 PRODUCT NAME: BREAKTHROUGH SATIN WROUGHT IRON BLACK

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike and contain spill with inert materials (sand, clay, earth, etc.).  
Transfer the liquid to containers for recovery or disposal. Keep spill  
out of sewers and open bodies of water.

WASTE DISPOSAL METHOD

Dispose of in accordance with all local, state, and federal  
requirements.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep from freezing. Keep away from heat and open flame. Avoid  
breathing vapor. Avoid contact with eyes, skin and clothing. Use with  
ventilation adequate to maintain vapor concentration below the TLV.  
Containers of product may be hazardous when emptied--all hazard  
precautions must be observed. KEEP OUT OF REACH OF CHILDREN!

OTHER PRECAUTIONS

Hazardous ingredients notated in Section II as "subject to Sec. 313" are  
subject to reporting requirements under Section 313 of the Emergency  
Planning & Community Right-to-Know Act of 1986 and of 40 CFR 372. This  
information must be included on all MSDS's that are copied and  
distributed for this product.

===== SECTION VIII - CONTROL MEASURES =====  
50 90 PRODUCT NAME: BREAKTHROUGH SATIN WROUGHT IRON BLACK

RESPIRATORY PROTECTION

Where adequate ventilation is maintained, the use of respiratory

equipment is not necessary. However, if the TLV of the product or any component is exceeded, use a MSHA-NIOSH approved respirator.

VENTILATION

Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

PROTECTIVE GLOVES

For repeated contact, use impervious gloves.

EYE PROTECTION

Chemical goggles are not required when adequate ventilation is maintained. Use goggles if eye discomfort is experienced.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

To prevent repeated or prolonged skin contact, wear impervious clothing and shoes.

WORK/HYGIENIC PRACTICES

Remove contaminated clothing immediately. Wash skin area with soap and water. Launder clothes before reuse.

===== SECTION IX - DISCLAIMER =====

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originated with Vanex or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.