

**1 Identification of the substance/preparation and of the company/undertaking**

- Product details
- Trade name: Epifanes Woodfinish Matte
- Application of the substance / the preparation Satin varnish alternative
- Manufacturer/Supplier:  
W.Heeren & Zoon BV  
P.O. Box 166  
Netherlands  
Phone:(++31)297 360366  
Fax :(++31)297 342078
- Further information obtainable from: Environment protection department.
- Information in case of emergency: Zie onder rubriek Fabrikant/leverancier

**2 Composition/information on ingredients**

- Chemical characterization
- Description:  
Resin mixture  
Solvent mixture with additives  
Mixture of synthetic binders, matting agent, additives  
and organic solvents

## • Dangerous components:

CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	25-50%
EINECS: 265-150-3	Xn; R 10-65-66	

- Additional information:  
For the wording of the listed risk phrases refer to section 16.

**3 Hazards identification**

- Hazard description: Not applicable.
- Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.  
R 10 Flammable.  
R 66 Repeated exposure may cause skin dryness or cracking.
- Classification system:  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**4 First-aid measures**

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

Trade name: Epifanes Woodfinish Matte

(Contd. of page 1)

**5 Fire-fighting measures**

- Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Protective equipment: No special measures required.

**\* 6 Accidental release measures**

- Person-related safety precautions:  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:  
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.

**\* 7 Handling and storage**

- Handling:
- Information for safe handling:  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

**\* 8 Exposure controls/personal protection**

- Additional information about design of technical facilities:  
No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- Respiratory protection:  
Suitable respiratory protective device recommended.  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 3)

Trade name: Epifanes Woodfinish Matte

(Contd. of page 2)

- Protection of hands:  
Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Tightly sealed goggles

## 9 Physical and chemical properties

### • General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

### • Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	150°C

• Flash point: > 42°C

• Ignition temperature: 240°C

• Self-igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

### • Explosion limits:

Lower:	0.6 Vol %
Upper:	7.0 Vol %

• Vapour pressure at 20°C: 1 hPa

• Density at 20°C: 0.93 g/cm<sup>3</sup>

• Solubility in / Miscibility with water: Not miscible or difficult to mix.

### • Viscosity:

Kinematic at 20°C: 35 s (ISO 6 mm)

### • Solvent content:

Organic solvents:	47.3 %
VOC content:	47.3 %
	439.3 g/l / 3.67 lb/gal

(Contd. on page 4)

Printing date 14.03.2007

Reviewed on 02.02.2007

Trade name: Epifanes Woodfinish Matte

(Contd. of page 3)

• Solids content: 51.9 % (SC % 1h150 C)

**10 Stability and reactivity**

- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.
- Dangerous decomposition products: No dangerous decomposition products known.

**11 Toxicological information**

- Acute toxicity:

- LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 &gt;5000 mg/kg (rat)

Dermal LD50 &gt;3000 mg/kg (rab)

96-29-7 2-butanone oxime

Oral LD50 3700 mg/kg (rat)

Dermal LD50 200-2000 mg/kg (rat)

Inhalative LC50/4 h 20 mg/l (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

**12 Ecological information**

- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**13 Disposal considerations**

- Product:
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

**14 Transport information**

- Land transport ADR/RID (cross-border)
- ADR/RID class: 3 Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1263

(Contd. on page 5)

Printing date 14.03.2007

Reviewed on 02.02.2007

Trade name: Epifanes Woodfinish Matte

(Contd. of page 4)

- Packaging group: III
- Hazard label 3
- Description of goods: 1263 PAINT

- Maritime transport IMDG:
- IMDG Class: 3
- UN Number: 1263
- Label 3
- Packaging group: III
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: PAINT

- Air transport ICAO-TI and IATA-DGR:
- UN/ID Number: 1263
- Label 3
- Packaging group: III
- Proper shipping name: PAINT

**15 Regulatory information**

- Labelling according to EU guidelines:  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- Risk phrases:  
10 Flammable.  
66 Repeated exposure may cause skin dryness or cracking.
- Safety phrases:  
2 Keep out of the reach of children.  
23 Do not breathe fumes/aerosol.  
24 Avoid contact with skin.  
46 If swallowed, seek medical advice immediately and show this container or label.  
51 Use only in well-ventilated areas.
- Special labelling of certain preparations:  
Contains 2-butanone oxime, cobalt carboxylate. May produce an allergic reaction.
- National regulations:
- Technical instructions (air):

Class	Share in %
I	≤ 2,5
NK	25-50

- Waterhazard class:  
Water hazard class 1 (Self-assessment): slightly hazardous for water.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 6)

Printing date 14.03.2007

Reviewed on 02.02.2007

Trade name: Epifanes Woodfinish Matte

(Contd. of page 5)

- Relevant R-phrases
  - 10 Flammable.
  - 65 Harmful: may cause lung damage if swallowed.
  - 66 Repeated exposure may cause skin dryness or cracking.
- Department issuing MSDS: Environment protection department.
- Contact: J.J. van Dijk
- \* Data compared to the previous version altered.

GB